

TurboCord

Portable Electric Vehicle Charger



Model TurboCord (240V), TurboCord Dual (120V & 240V)

Powerful. Flexible.

The dual-voltage model works with both a 120V standard outlet or a higher power 240V outlet for faster charging. In Level 2/240V mode, it charges up to 3x faster than the standard 120V cordset.

Compact. Simple.

Provides the flexibility and freedom to take it anywhere. Just plug it directly into an outlet and charge at home, work, or play.

Safe. Reliable.

Uses state-of-the-art safety features, including temperature monitoring and auto shut-off if there is an issue. It is the only UL Listed dual-voltage plug-in charger on the market.

Key Features:

- State-of-the-art safety features
- Compact portable Level 2 charger
- 240V mode charges up to 3x faster than 120V cordset
- Dual voltage model works with 120V and 240V outlet
- Auto shut-off if an issue is detected
- Temperature monitoring
- Super rugged NEMA 6P weatherproof enclosure
- Simple installation - all you need is a 240V NEMA 6-20 outlet
- Easy to use, simply plug-in and charge
- UL and cUL certified

Technical Specifications

	TurboCord DUAL 120V/240V	TurboCord 240V
Voltage	120V / 240V	240V
Output Power	12A continuous @ 120V 16A continuous @ 240V	16A continuous @ 240V
Circuit Breaker Rating	15A @ 120V 20A @ 240 / 208V	20A @ 240V / 208V
Frequency	60Hz	60Hz
Plug Type	NEMA 6-20P direct plug-in	NEMA 6-20P direct plug-in
Cable Length	20 ft (6.1m)	20 ft (6.1m)
Weight	4 lbs (1.81 kg) - module 0.2 lbs (0.09 kg) - adapter	4 lbs (1.81 kg)
Operating Temperature	-40C (-40°F) to +50C (122°F)	-40C (-40°F) to +50C (122°F)
Indoor / Outdoor	Yes NEMA 6P watertight	Yes NEMA 6P watertight
Charge Coupler	SAE J1772 compliant	SAE J1772 compliant
Certification	UL and cUL	UL and cUL



Webasto Charging Systems, Inc.
800 Royal Oaks Dr, Suite 210
Monrovia, CA 91016
USA

+1 (888) 833-2148
evscs@webasto.com



Industrial Battery Products
1250 Ambassador Blvd.
St. Louis, MO 63132
Phone: (888) 813-5636
ibpreservepower.com



evsolutions.com